

新加坡环保与卫生协会(EMAS)期刊

2012年4月刊

1003 BUKIT MERAH CENTRAL, #02-10, SINGAPORE 159836 WWW.EMAS.ORG.SG

2012年4月 EMAS 的公告

一月及二月在今年早些时候的忙碌奔波,三月的活动方面也比较安静。但我们有两个成员的事件更新,在三月份进展情况。

- 1. EXCO 会议于 3 月 9 日
 - a. 讨论即将举行的活动和周围的组织秘书处的细节。即香港之行,在阿德莱德 ISSA interclean 和 FAOPMA。需要接近和发掘海外旅行提供资金的可能性进行讨论,鉴于 我们的行业是此类事件的预算将由于较低的利润率高于其他行业的低。
 - b. 目前的状况是,劳动力发展局不资助等海外游和 IE 新加坡还没有批准到香港的行程,因为他们不觉得有足够的业务,为那些寻求去旅行的范围匹配。然而,EMAS 将重新访与 IE 新加坡在稍后的日期。
 - c. e2i 现仍在考虑,并没有恢复任何一种方式尚未。
 - d. 该协会是希望政府支持,以协助企业通过协会,探索新技术,以及允许企业探索海外扩 张的可能性。
 - e. 另外还有个后验尸讨论 EMAS 的保龄球比赛,并认为在未来的改进提出了一些建议。 EMAS 的成员可以看一下对更多这样的精彩赛事,以及涉及到双方的成员公司及其工作 人员。EMAS 希望与秘书处密切合作,提高对此类事件的组织。
- 2. 在 3 月 10 日同 RAS 的会议-
 - I. 要探索做一个像高尔夫球比赛,看看是否有协同作用可以来约,从合作的联合活动。到目前为止,这仍然是在讨论之中。

海峡时报条清洁及灭虫行业的合同,并于2012年3月31日公布的工人特征。如果错过了,请找到您的阅读所附文章。

我们希望这将是在塑造服务购房者的心态,积极的一步。也希望,这将是有益的,以展示在我们这个行业的公司,更积极,并显示同时有是一个需要付出更多,因此,许多公司都有限制他们可以取得的。

在此期间,EMAS 将继续朝着建设一个行业,是能够把重点放在提高技术和工作流程,以及提高专业,工人从而能达到更高的工资在同行业中。

最后,本月初,EMAS 为成员提供给 3M,建筑和商业事务司提出了一个特别的促销。公司提供 EMAS 成员 10%折扣在他们的 Scotchguard™石楼保护。有兴趣人士可见连接式广告和公司直接 联系。此外,我们有特殊的另一个从 Klenco 新加坡促销,从即日起至 6 月。他们的 Toolflex 工具,存储系统有买 3 送 1 的促销。请参阅附着式广告的信息。

新加坡环保与卫生协会 期刊 第2页







Toolflex Aluminum Rail Tools Storage System

- · Series of simple and flexible equipment holders
- · Facilitates the storage of handle-equipped tools
- · Easy to hang or take down with just one hand and even keep heavier tools in place
- · Ingenious design allowing gap between two holders to be adjusted according to the size of tools
- . Optional hook can be added to the rail to optimize the use of the system

KLENCO (SINGAPORE) PTE LTD

18 Gul Crescent, Singapore 629527 ● Tet. (65) 6862 3388 ● Fax: (65) 6861 7575 ● sales@klenco-asia.com ● www.klenco-asia.com
Company Registration No. 197100402R

Singapore ● China ● Malaysia ● Thailand ● ASEAN ● South Asia

新加坡环保与卫生协会 期刊____ 第3页





Introducing Scotchgard™ Stone Floor Protector

It delivers a highly durable seal with less labor – and a significantly higher return on investment.

In just one to two coats, Scotchgard™ Stone Floor Protector produces a clean, shiny finish that is less susceptible to scuffs and scratches. Dust, chemical, and water resistant, it lasts for up to a year with minimal maintenance.

That means you will spend less of your operations budget on labor and floor finishing chemicals, without sacrificing your glossy floors.

3M™ Trizact™ Diamond HX Disc

These new discs have been designed for use with the Scotchgard™ Stone Floor Protector System. 3M™ Trizact™ Diamond HX discs can help turn your dull and scratched stone floors into beautiful and shiny floors. Used for surface preparation, only one-time use.


Benefits

Produces a glossy, hard, dust repellent, chemical-resistant and watertight surface with anti-slip properties (with NFSI Certification), giving a cleaner, shinier and safer floor! No stripping required.



Scotchgard™ Stone Floor Protector





Trizact™ Diamond Discs

3M Scotchgard Stone Floor Protector



Applications:



standard speed, high speed or ultra high speed equipment and pads





National Floor Safety Institute (NFSI) Certification of Scotchgard™ Stone Floor Protector

Scotchgard™ Stone Floor Protector was recently submitted to NFSI for testing to be certified as providing "high-traction". NFSI product certification is intended to provide product manufacturers the means to have their products independently evaluated for wet slip resistance.

NFSI evaluation consisted of the following process:

- Scotchgard™ Stone Floor Protector was installed in a real world (Test Site) application and maintained for 30 days
- After the 30 day test period, Scotchgard[™] Stone Floor Protector was tested in accordance with ANSI B101.1 (Test Method for Measuring Wet SCOF of Common Hard-Surface Floor Materials).

The NFSI evaluation of Scotchgard™ Stone Floor Protector determined the wet static coefficient of friction (SCOF) was greater than 0.60. Based on the SCOF value, Scotchgard™ Stone Floor Protector has been certified by NFSI as providing "high-traction".

A wet SCOF of greater than 0.60 was chosen by NFSI as the criteria for "high traction" because according to NFSI, floor surfaces maintaining this level of slip resistance when wet have proven to reduce slip-and-fall claims by between 50% and 90%. ANSI B101.1 specifies three traction ranges according to the measured wet SCOF: High Traction, Moderate Traction, and Minimal Available Traction. The three ranges are summarized in the table below taken from the ANSI/NFSI B101.1-009 Standard.

Wet SCOF Value (µ)	Available Traction	Remediation
μ≥0.60	High Traction - Lower probability of slipping	Monitor SCOF regularly and maintain cleanliness.
0.40 ≤ μ <0.60	Moderate Traction - Increased probability of slipping	Monitor SCOF regularly and maintain cleanliness. Consider traction- enhancing products and technologies.
μ < 0.40	Minimal Available Traction - Higher probability of slipping	Seek professional intervention. Consider replacing flooring and/or coating with high-traction products.

3M Building & Commercial Services Division Tel: 6450 8888 / 6450 8818 www.3M.com.sg/cleaning

我们很高兴延长为我们的会员独家优惠 EMAS 找到我们协会的成员,我们希望有兴趣的成员将利用这些特殊优惠的优势!